



AN 056: Using the Titanium LPDDR4 Debug Tool Example

AN056-v2.3
July 2025
www.efinixinc.com



Contents

Introduction.....	3
Download the LPDDR4 Debug Tool Example Design to the Board.....	3
Running the LPDDR4 Debug Tool Example Design.....	4
LPDDR4 Debug Tool Arguments and Options.....	7
Using the LPDDR4 Debug Tool with Your Board.....	9
Revision History.....	9

Introduction

In memory management and performance optimization, precise settings play a crucial role in ensuring optimal system operation and reliability. Efinix provides a Python-based LPDDR4 Debug Tool example design for use with either the Titanium Ti375C529 Development Board, Titanium Ti375N1156 Development Board, Titanium Ti180 M484 Development Board, or Titanium Ti180 J484 Development Board. Use the example design to demonstrate how to use the LPDDR4 Debug Tool to help you obtain the optimal settings and debug the LPDDR4 controller in supported Titanium FPGAs.

Features

- Memory initialization and I/O calibration
- CA training
- Write leveling
- Gate training
- Read leveling
- Write DQ training
- Hardware memory tests with linear feedback shift register (LFSR) data patterns
- Valid timing window observation with memory test
- Mode Register Read (MRR) and Mode Register Write (MRW)



Learn more: Refer to [Using the LPDDR4 Debug Tool with Your Board](#) on page 9 for more information when you want to use the LPDDR4 Debug Tool with other boards.

Hardware and Software Requirements

- Titanium Ti375C529 Development Board, Titanium Ti375N1156 Development Board, Titanium Ti180 M484 Development Board, or Titanium Ti180 J484 Development Board
- USB cable
- Terminal software
- Efinity software v2025.1.110.1.5 or later (required for recompilation)

Download the LPDDR4 Debug Tool Example Design to the Board

The memory efficiency tester includes a bitstream file to get you started quickly. Download it to the board using these steps:

1. Download the file **ti_lpddr4_debug_tool-v<version>.zip** from the Support Center.
2. Connect the development board to your computer using a USB cable.
3. In the Efinity Programmer, under Programming Mode, select **SPI Active using JTAG Bridge**.
4. Under **Image**, click the **Select Image File** button and select **tools_core.hex** file located in the **ti_lpddr4_debug_tools\bsp\<device>** directory.
5. Click the **Start Program** button.

Running the LPDDR4 Debug Tool Example Design

To run LPDDR4 Debug Tool:

1. Set up your Efinity environment:
 - a) Open a terminal and change to the Efinity installation directory.
 - b) Type the following command and press Enter:
 - Linux— `source bin/setup.sh`
 - Windows— `bin\setup.bat`
2. In the terminal, change the path to: `ti_lpddr4_debug_tools\bsp\<dev>`.
3. Type the following command and press Enter: `efx_run tools_core.xml --flow interface` (to generate the interface file, only necessary for the first time).
4. In the terminal, change to the extracted LPDDR4 Debug Tool directory.
5. Run the **console.py** with the tool option and if applicable, the options arguments, then press enter. See [LPDDR4 Debug Tool Arguments and Options](#) on page 7 for the list of available options and arguments.

Example 1: Execute the Program

```
python3 console.py --dev TI180J484

=====
=====EFINIX LPDDR4 Utility v2.0=====
=====

Type: LPDDR4x
Data width: 16
Density: 4G bit
Frequency: 1066 Mhz
Rank: 1
Chip Select Map: 1
AXI1: 66.67 Mhz

--> Calibration item Menu:
----> init      LPDDR4 initialization
----> io        I/O Calibration
----> calvl     CA Training
----> wrlvl     Write Leveling
----> gatlvl    Gate Leveling
----> rdlvl     Read Leveling
----> wdqlvl    Write DQ Leveling
----> all       Run all above process

--> Memory Quick Test Menu:
----> mtest4    4MB      Size Memory Test
----> mtest16   16MB     Size Memory Test
----> mtest32   32MB     Size Memory Test
----> mtest64   64MB     Size Memory Test
----> mtest128  128MB    Size Memory Test
----> mtest256 256MB    Size Memory Test
----> mtest512 512MB    Size Memory Test
----> mtest1024 1024MB  Size Memory Test

--> Memory efficiency Test Menu:
----> eff Default Memory efficiency Test

--> Others Option:
----> mrw LPDDR4 Mode Register Write
----> mrr LPDDR4 Mode Register Read

Select Option:
```

Example 2: Run All

```

>Select Option: all
Read Memory controller ID PASS
Read pi controller ID PASS
---DDR Initialization---
cs mapping = 1
Write CTL Register
Write PHY Register
Write PI Register
PLL locked
MC Initialization Done
PI PLL = True
---DDR Initialization Done---
---I/O Calibration---
IO pass 1 calibration done
IO pass 2 calibration done

CA Training result in (ps)
||===== CA =====||===== MIN =====||===== MAX =====||===== CENTER =====||===== EYE WIDTH =====||===== EYE
WIDTH% =====||
|| CA0          ||          1088.33 ||          1830.37 ||          1459.35 ||          742.04 ||          79
||
[-----o-----]
|| CA1          ||          1071.84 ||          1835.86 ||          1453.85 ||          764.03 ||          81
||
[-----o-----]
|| CA2          ||          1077.33 ||          1830.37 ||          1453.85 ||          753.03 ||          80
||
[-----o-----]
|| CA3          ||          1066.34 ||          1797.39 ||          1431.87 ||          731.05 ||          77
||
[-----o-----]
|| CA4          ||          1055.35 ||          1764.41 ||          1409.88 ||          709.06 ||          75
||
[-----o-----]
|| CA5          ||          1099.32 ||          1835.86 ||          1467.59 ||          736.54 ||          78
||
[-----o-----]
MR12 = 0x20
CS0 Vref CA = 22.8% Range = 0
MR12 = 0x20
CS2 Vref CA = 22.8% Range = 0
---Write Leveling---
Write DQS Delay Slice0 = 120.93ps
Write DQS Delay Slice1 = 109.93ps
---Gate Leveling---
Gate DQS Delay slice 0 = 3832.96 ps
Gate DQS Delay slice 1 = 3832.96 ps

---Read Leveling---
Rising Read leveling result in (ps)
||===== DQ =====||===== MIN =====||===== MAX =====||===== CENTER =====||===== EYE WIDTH =====||===== EYE
WIDTH% =====||
|| DQ0          ||          43.97  ||          461.71 ||          252.84 ||          417.74 ||          89
||
[-----o-----]
|| DQ1          ||          65.96  ||          461.71 ||          263.83 ||          395.76 ||          84
||
[-----o-----]
|| DQ2          ||          43.97  ||          461.71 ||          252.84 ||          417.74 ||          89
||
[-----o-----]
|| DQ3          ||          43.97  ||          461.71 ||          252.84 ||          417.74 ||          89
||
[-----o-----]
|| DQ4          ||          21.99  ||          461.71 ||          241.85 ||          439.73 ||          93
||
[-----o-----]
|| DQ5          ||          65.96  ||          461.71 ||          263.83 ||          395.76 ||          84
||
[-----o-----]
|| DQ6          ||          43.97  ||          461.71 ||          252.84 ||          417.74 ||          89
||
[-----o-----]
|| DQ7          ||          87.95  ||          461.71 ||          274.83 ||          373.77 ||          79
||
[-----o-----]
|| DQ8          ||          21.99  ||          439.73 ||          230.86 ||          417.74 ||          89
||
[-----o-----]
|| DQ9          ||          65.96  ||          439.73 ||          252.84 ||          373.77 ||          79
||
[-----o-----]

```

```

|| DQ10 || 21.99 || 439.73 || 230.86 || 417.74 || 89
||
[-----]
|| DQ11 || 87.95 || 439.73 || 263.84 || 351.78 || 75
||
[-----]
|| DQ12 || 43.97 || 461.71 || 252.84 || 417.74 || 89
||
[-----]
|| DQ13 || 65.96 || 439.73 || 252.84 || 373.77 || 79
||
[-----]
|| DQ14 || 43.97 || 439.73 || 241.85 || 395.76 || 84
||
[-----]
|| DQ15 || 87.95 || 461.71 || 274.83 || 373.77 || 79
||
[-----]

Falling Read leveling result in (ps)
||===== DQ =====||===== MIN =====||===== MAX =====||===== CENTER =====||===== EYE WIDTH =====||===== EYE
WIDTH% =====||
|| DQ0 || 21.99 || 329.8 || 175.9 || 307.81 || 65
||
[-----]
|| DQ1 || 43.97 ||

```

LPDDR4 Debug Tool Arguments and Options

You use the **main.py** script's arguments and options to run and customize the LPDDR4 Debug Tool features.

init

Usage	<code>init</code>
Options	-
Description	Run DDR initialization.

io

Usage	<code>io</code>
Options	-
Description	Run I/O calibration.

calvl

Usage	<code>calvl</code>
Options	-
Description	Run CA leveling.

wrlvl

Usage	<code>wrlvl</code>
Options	-
Description	Run write leveling.

gatlvl

Usage	<code>gatlvl</code>
Options	-
Description	Run gate leveling.

rdlvl

Usage	<code>rdlvl</code>
Options	-
Description	Run read leveling.

wdqlvl

Usage	<code>wdqlvl</code>
Options	-
Description	Run write DQ leveling.

mtest<size>

Usage	mtest<size>
Options	Test size
Description	Run hardware memory test with a data pattern.

mrr

Usage	mrr <addr>
Options	<ADDR>: Mode register address to read
Description	Read the mode register.

mrw

Usage	mrw <ADDR> <DATA>
Options	<ADDR>: Mode register address to write to <DATA>: Data to be written
Description	Write to the mode register.

all

Usage	all
Options	-
Description	Run full calibration with a single argument consisting of init, io, calvl, wrlvl, gatlvl, rd1vl, and wdq1vl.

eff

Usage	eff
Options	-
Description	Run memory efficiency test.

Using the LPDDR4 Debug Tool with Your Board

You need to modify some settings and recompile the LPDDR4 Debug Tool project file (**tools_core.xml**) if you want to use it for boards other than the Titanium Ti180 J484 Development Board. After modifying the settings, recompile the project with Efinity software v2025.1.110.1.5 or later. The following table summarizes the changes that you must consider:

Settings	Description
PLL Settings	Modify the PLL resource and output clock according to your board design in the Interface Designer.
Project Settings	Select your FPGA in the Efinity Project Editor.

Copy the defaulted project folder from **/bsp** and modify the new name that you want.

Example:

```
python3 console.py --dev<new_name>
```

Revision History

Table 1: Document Revision History

Date	Version	Description
July 2025	2.3	Update Hardware and Software Requirements on page 3. (DOC-2637) Update Download the LPDDR4 Debug Tool Example Design to the Board on page 3. (DOC-2637) Update Running the LPDDR4 Debug Tool Example Design on page 4. (DOC-2637) Update Using the LPDDR4 Debug Tool with Your Board on page 9. (DOC-2637)
April 2025	2.2	Update Introduction on page 3. (DOC-2501) Update Hardware and Software Requirements on page 3. (DOC-2501) Update Download the LPDDR4 Debug Tool Example Design to the Board on page 3. (DOC-2501)
August 2024	2.1	Fixed typo in Running the LPDDR4 Debug Tool Example Design on page 4. (DOC-2007)
January 2024	2.0	Added Ti180 J484 Development Board in Introduction and Hardware and Software Requirements. (DOC-1667) Updated section LPDDR4 Debug Tool Arguments and Options and Using the LPDDR4 Debug Tool with Your Board. Updated file location in section Download the LPDDR4 Debug Tool Example Design to the Board.
July 2022	1.0	Initial release.